

**Description****EMULSIFIABLE OIL TO PROCESS COPPER**

Extremely sophisticated paraffin-based emulsifier. With synthetic, unctuous media, emulgent additives and corrosion inhibitors.

Details

Product specifications		ADVANTAGES
High cutting performance		Durable Tools
High stability		Even with hard water
IP 287 at 3%		Protection against corrosion
Anti-foam		Even under pressure
Physical-Chemical Properties		Emulsion
Colour (ASTM D1500)	Concentrated product Max. 4-5	Milky fine
Specific weight	0.940 kg/l	
pH value at 5%		9.0
Refractometric Factor		1
IP 287		3%
Mineral Oil Content	65%	

Important notes:

One of the best metal-working fluids to use with copper and brass

.

Concentrations for Use**Operations**

Copper and its alloys

Aluminium

Percentage in Water

From 5% to 8%

From 5% to 10%

Packaging available

30-210l

The information in this technical sheet is based on the specifications and potential use known to us. However, this data does not imply any legal obligation or liability whatsoever.

REGISTERED OFFICE
Via Domenico Scarlatti, 26
20124 Milan



Commercial Offices and Plant
Corso Europa, 91 – 20020 Solaro (MI)
info@farmicol.com
Customer Service +39 02 84505409
www.faren.com