



## Description

**HEAVY DUTY EMULSIFIABLE OIL**

It has strong characteristics of extreme pressure. It is, therefore, ideal in all processes of heavy-duty grinding on aluminium alloy and ferrous materials.

## Details

## Product specifications

High cutting performance

High stability

 IP 287 at 3%  
Free from: Secondary amines  
and Boron

## ADVANTAGES

Durable Tools

Safe and economic to use

Protection against corrosion

Good skin compatibility

## Physical-Chemical Properties

Colour (ASTM D1500)

Specific weight

pH value at 5%

Refractometric Factor

IP 287

Mineral Oil Content

## Concentrated product

Max. 4.5

0.990 kg/l

## Emulsion

Milky

9.3

1

3%

42%

## Important notes:

Cutting-edge for heavy-duty operations

## Concentrations for Use

## Operations

Steels and Cast Iron

Aluminium

## Percentage in Water

From 5% to 6%

From 5% to 10%

## Packaging available

5-30-210l

The information in this technical sheet is based on the specifications and potential use known to us. However, this data does not imply any legal obligation or liability whatsoever.

 REGISTERED OFFICE  
Via Domenico Scarlatti, 26  
20124 Milan

 Commercial Offices and Plant  
Corso Europa, 91 – 20020 Solaro (MI)  
[info@farmicol.com](mailto:info@farmicol.com)  
Customer Service +39 02 84505409  
[www.faren.com](http://www.faren.com)