



Description

CYANOACRYLATE FOR POROUS MATERIALS

Details

For absorbent materials (leather, cork, soft wood, porous rubber, ferrite, ceramics, porcelain, plastic foam), vertical surfaces, surfaces with a tolerance of up to 0.20 mm Enables pieces to be mended within seconds.

PHYSICAL-CHEMICAL AND TECHNICAL PROPERTIES

Properties	Description
Appearance	Transparent liquid
Specific weight	1.08 kg/l
Viscosity	1500 mPa.s
Shear resistance	220 N/mm ²
Reaction speed	20-120"
Flash point	>85°C
Maximum Slack	0.20mm
Temperature resistance	-50 > +80°C

Surfaces	Gluing times
Steel/steel	<40"
Abs/abs	<20"
Aluminium-aluminium	<30"
Rubber/rubber	<10"
Pvc/pvc	<20"

Important notes:

Chemical resistance

Good resistance to oils and solvents, diesel oil, ethanol, propanol and freon. Not recommended in systems transporting oxygen. Do not use if chlorinated compounds or other highly oxidant chemical products are present.

Recommendations for use

Correctly align the parts to be glued. Ensure the parts are clean and dry. Apply the product directly from the can. Spread a small quantity on one surface only and press the parts firmly together.

N.B.: The less you use, the faster the parts will glue together.
Shelf-life: 12 months in a cool place (ideal temperature +5°C)

Packaging available

20-50 g

The information in this technical sheet is based on the specifications and potential use known to us. However, this data does not imply any legal obligation or liability whatsoever.