09-2019

DETERGENT – FOAMING DEGREASER

DESCRIPTION

Medium alkaline detergent suitable for wash tanks, washing floors machineries and excellent for separators and oil industry environment.

- Soluble in water
- Excellent degreasing action
- Does not develop any foam even if subject to strong beating
- Enriched with sequestrants which prevent limescale deposits and filters blocks.

SUGGESTIONS AND WAY OF USE

Separators in oil industry: 3-10% in hot water at about 50°C. Let the solution circulating in separator for minimum 15 minutes. Rinse for almost 2 times with hot and clean water to eliminate any residual. For general cleaning, from 1 to 5% in water.

Wash tanks: at 1% with water. Heat the solution up to 50-60°C.

Floors washing machines: from 3 to 10% in water in the tank

Sifters: from 1 to 2% in water, also cold.

Ultrasounds washing machines: prepare a solution at 20% with water

Note: Always test in advance compatibility between product and heavy alloys

Packaging: 10 kg

CHEMICAL-PHYSICAL PROPERTIES

| Aspect and color | Yellowish liquid |
|------------------|------------------|
| Density | 1,330 kg/l |
| PH value (at 3%) | 12.00 |
| Boiling point | >100°C |

Le indicazioni della presente scheda tecnica si basano sulle caratteristiche e potenzialità di utilizzo a noi conosciute. In generale non è però possibile dedurre da questi dati un obbligo o responsabilità legale alcuna.





