



Description

TRANSPARENT SILICONE GREASE

Details

To lubricate valves, taps, chains, roller tables, mould anti-adhesive, electric and electronic assembly, insulators, joints, brackets, seals, vacuum bell-jar covers, probes.

PHYSICAL-CHEMICAL AND TECHNICAL PROPERTIES

| Properties | Description | Properties | Description |
|-----------------------------|-------------|---------------------------|-------------|
| Appearance | Ointment | Acid and alkali resistant | Good |
| Colour | Translucent | Humidity resistant | Excellent |
| Density at 20°C | 0.970 | Sea water resistant | Excellent |
| Dielectric strength (kw/mm) | >=15 | Polar solvent resistant | Excellent |
| Temperature intervals | -50°/+250°C | | |

Important notes:

- Chemically safe and inert
- Water repellent
- Excellent humidity resistance
- Antistatic
- Resists soft and salt, hot and cold water, condensate, weak acids and alkali.
- High dielectric strength which makes it suitable as a dielectric seal for live equipment.

Directions for use

Clean the parts to be treated from any residue of grease or lubricant used previously.
Evenly apply with a spatula or hard bristle brush to the required thickness.

Packaging available

125-500-1000ml

The information in this technical sheet is based on the specifications and potential use known to us. However, this data does not imply any legal obligation or liability whatsoever.