

**Description****COPPER-BASED GREASE**

Specific for high temperatures (over 1,000°C) or as a lubricant under conditions of Extreme Pressure. It can be used in all situations requiring excellent anti-seize, anti-corrosion and lubricant strength with very heavy loads.

Details**PHYSICAL-CHEMICAL AND TECHNICAL PROPERTIES**

Properties	Description	Properties	Description
Appearance	Soft, tacky	Corrosion test ASTM D743	Pass
Colour	Coppery		
Specific weight	0.990		
Dielectric strength (kw/mm)	>=15		
Penetration ASTM D217	265/295		
Drop point ASTM D566	Infusible		

Important notes:

- Protects threads from corrosion, wear, deformation, breaking and seizing.
- Wash and salt water resistant
- Inert to the majority of gases
- Resists temperatures up to + 1000 +/- 1100°C and extreme pressure.
- Ideal for ship and automobile bolts, bolts and joints of high temperature oil pumps, bolts and cables for construction equipment, as a lubricant in steel works, for agricultural machines.

Directions for use

Clean the parts to be treated from any residue of grease or lubricant used previously.
Evenly apply with a spatula or hard bristle brush to the required thickness.

Packaging available

750ml

The information in this technical sheet is based on the specifications and potential use known to us. However, this data does not imply any legal obligation or liability whatsoever.