



## Description

## LITHIUM GREASE

Guarantees perfect lubrication and anticorrosive protection over time. In the automobile, nautical, construction and agricultural sectors.

## Details

## Product specifications

## INFO

DEWATERING

Resists water and sea water

UNIVERSAL.

For any type of lubrication

MECHANICAL STABILITY

Guaranteed even with vibrations

## Physical-Chemical Properties

Colour and Appearance

## Product in its physical state

Beige liquid

Specific weight

0.68 kg/l

Fragrance

Characteristic

## Recommended use

Contains pure lithium grease, fatty acid synthetic esters and special adhesives with mixtures of refined oils. Resists up to a temperature between 160-180°C. Perfect lubrication and anticorrosive protection over time. UNIVERSAL

## HOW TO USE

Shake the aerosol and directly spray the surface from a distance of approximately 20 cm.

## Packaging available

400ml Spray

The information in this technical sheet is based on the specifications and potential use known to us. However, this data does not imply any legal obligation or liability whatsoever.

REGISTERED OFFICE  
Via Domenico Scarlatti, 26  
20124 Milan



Commercial Offices and Plant  
Corso Europa, 91 – 20020 Solaro (MI)  
[info@farmicol.com](mailto:info@farmicol.com)  
Customer Service +39 02 84505409  
[www.faren.com](http://www.faren.com)