

**Description****LUBRICATING OIL FOR AIR COMPRESSORS**

Ideal for lubricating rotary compressors, especially the screw type, with high operational temperatures. "Ashless" additives that considerably reduce the tendency to form deposits. Excellent anti-wear properties and high filtration level.

Details**Alternative Compressors****Rotary Compressors****Standard compliant****Standard compliant**

ISO L – DDA – DAB

ISO L – DAG - DAH

DIN 51351 – TEIL 2

DIN 51506 VD-L

Physical-Chemical Properties

	ISO 68	ISO 100	ISO 100	METHOD
Liquid Appearance	clear	clear	clear	
Colour	L 1.5	L 2.0	L 2.5	ASTM D1500
Specific weight at 15° C kg/l	0.870	0.885	0.890	ASTM D1298
Viscosity 40°C cSt	68	100	220	ASTM D445
Flash point °C	240°C	270°C	290°C	ASTM D92
Pour point	-27°C	-24°C	-21°C	ASTM D97

Specific Applications

Particularly suitable for lubricating rotary compressors, especially the screw type, with high operational temperatures (> 120°C).

Suitable for static or mobile groups operating at ambient temperatures between -20°C and + 50°C.

Packaging available

25-210l

The information in this technical sheet is based on the specifications and potential use known to us. However, this data does not imply any legal obligation or liability whatsoever.

REGISTERED OFFICE
Via Domenico Scarlatti, 26
20124 Milan



Commercial Offices and Plant
Corso Europa, 91 – 20020 Solaro (MI)
info@farmicol.com
Customer Service +39 02 84505409
www.faren.com