



Description

UNIVERSAL EMULSIFIER

Details

Lubricant and Coolant which disperses in water creates a milky stable emulsion. Mineral base, ideal for medium works A base mineral, ideal for medium duty-work on ferrous and not ferrous materials

Product specifications

HIGH PERFORMANCE

HIGH STABILITY

IP 287 TO 3%
FREE FROM: Secondary
ammines, Phenols

ADVANTAGES

Durable tools

Economic over time

Protection against corrosion

Excellent skin compatibility

Physical-Chemical Properties

Colour (ASTM D1500)

Specific weight at 15°C

pH Value at 5%

Refractometric Factor

IP 287

Mineral Oil Content

Concentrated Product

Max. 2,5

0,970 kg/lt

Emulsion

Milky

9.2

1.0

3%

55%

Important notes

Logiq Cool EM has a cutting-edge formulation and is totally compliant with toxicology and health and hygiene legislation

Concentrations for Use

Operations

General

Medium-Severe

Percentage in water

From 3% to 7%

From 8% to 10%

Packaging available

5-25-210lt

The information in this technical sheet is based on the specifications and potential use known to us. However, this data does not imply any legal obligation or liability whatsoever.

REGISTERED OFFICE
Via Domenico Scarlatti, 26
20124 Milan



Commercial Offices and Plant
Corso Europa, 91 – 20020 Solaro (MI)
info@farmicol.com
Customer Service +39 02 84505409
www.faren.com