

**Description****ANTI-WEAR HYDRAULIC OIL**

Of superior quality, it complies with the international ISO EM classification. Formulated with extremely refined paraffin mineral oil and corrosion, anti-oxidant, anti-wear and anti-foam inhibitors.

Details**ADVANTAGES**

Excellent filtration characteristics even when humidity is present, and excellent system operativity.

Total absence of alterations during use, which lacquers and sludge may form, to guarantee a reduction in down time for extraordinary maintenance.

Physical-Chemical Properties

	ISO 32	ISO 46	ISO 68	METHOD
Liquid Appearance	clear	clear	clear	
Colour	L 1.0	L 2.0	L 2.5	ASTM D1500
Specific weight at 15°C kg/l	0.870	0.870	0.880	ASTM D1298
Viscosity 40°C cSt	32	46	68	ASTM D445
Flash point °C	210°C	228°C	240°C	ASTM D92
Pour point	- 27°C	- 27°C	- 24°C	ASTM D97

Specific Applications

- For hydraulic systems operating with high supply pressure, where a high anti-wear performance and excellent thermal-hydrolytic stability is required.
- Suitable for applications requiring a high level of filtration. (Solenoid valves, numerically controlled machine tools)
- Suitable to lubricate reducer gears and speed change gear without much stress load, flat and rolling bearings.

Packaging available

25-210l

The information in this technical sheet is based on the specifications and potential use known to us. However, this data does not imply any legal obligation or liability whatsoever.

REGISTERED OFFICE
Via Domenico Scarlatti, 26
20124 Milan



Commercial Offices and Plant
Corso Europa, 91 – 20020 Solaro (MI)
info@farmicol.com
Customer Service +39 02 84505409
www.faren.com