

**Description****MULTI-GRADE DIESEL ENGINE OIL**

Guarantees excellent operations with every type of diesel oil. Extends the intervals between oil changes according to what the manufacturers envisage and according to the level of use. The nature of the mineral base used and a package of modern additives give the product the highest level of oxidation stability and guarantee low levels of consumption and an excellent performance.

**Details****ADVANTAGES**

Suitable for use under any weather conditions. Guarantees protection for the engine for cold ignition and during long journeys.

**Physical-Chemical Properties**

|                               |        | METHOD     |
|-------------------------------|--------|------------|
| Appearance                    | Liquid |            |
| Colour                        | 4.5    | ASTM D1500 |
| Specific weight at 15° C kg/l | 0.880  | ASTM D1298 |
| Viscosity at 40° cSt          | 97     | ASTM D445  |
| Viscosity at 100°C cSt        | 15     | ASTM D445  |
| Viscosity Index               | 155    | ASTM D2270 |
| Flash point °C                | 210°C  | ASTM D92   |
| Pour point                    | -30    | ASTM D97   |

**Specific Applications****COMPLIES WITH THE FOLLOWING STANDARDS:**

- **API:** SG/CD
- **MIL-L:** 46152E/2104E

**Packaging available**

210l

The information in this technical sheet is based on the specifications and potential use known to us. However, this data does not imply any legal obligation or liability whatsoever.

REGISTERED OFFICE  
Via Domenico Scarlatti, 26  
20124 Milan



Commercial Offices and Plant  
Corso Europa, 91 – 20020 Solaro (MI)  
[info@farmicol.com](mailto:info@farmicol.com)  
Customer Service +39 02 84505409  
[www.faren.com](http://www.faren.com)