

**Description****GRAPHITE GREASE**

Infusible and with EP additive. Ideal to lubricate moving parts exposed to heat, earth moving, agricultural and construction machines.

**Details****PHYSICAL-CHEMICAL AND TECHNICAL PROPERTIES**

Properties	Description	Properties	Description
Appearance	Soft, tacky	Drop point ASTM D566	Not measurable
Colour	Black Graphite	Worked penetration	265/295 dmm
NLGI consistency number	2	ASTM D217	
Thickener type	Lithium	Corrosion on Copper IP	Negative
Temperature intervals	-20°/+180°C	112B	
		Sphere tests RIV 5h at 600	Below 10%
		Resistance to oxidation	Good

**Important notes:**

- Excellent anti-wear protection
- Maintains lubricant strength
- High stability of lubricant properties over time
- Is not washed away by water
- Wide operational temperature range
- Considerable mechanical stability and lubricant strength
- Good resistance to heavy loads and vibrations

**Directions for use**

Clean the parts to be treated from any residue of grease or lubricant used previously.  
Evenly apply with a spatula or hard bristle brush to the required thickness.

**Packaging available**

5 kg

The information in this technical sheet is based on the specifications and potential use known to us. However, this data does not imply any legal obligation or liability whatsoever.