



Description

WAX-BASED PROTECTIVE

Excellent industrial protective. Guarantees long-lasting protection, even outside. For any metal surface. Suitable for protecting metalwork and metal surfaces exposed for a long time to particularly corrosive weather conditions, such as fumes, acid rain or sea spray. Enables all situations to be faced. It is also suitable for large metal surfaces. Suitable to protect machinery in general, iron moulds in the sector of moulding plastic, metal, fibreglass, die-cast materials.

Details

ADVANTAGES

Guarantees outdoor protection for at least 6 months.

Excellent yield -15/20 m²/l (film of 20 micron). Remove with oil solvent.

Remains transparent and does not damage painted surfaces.

Universal - Motor vehicles, Boat engines, Earth moving machines, Tractors, etc.

Physical-Chemical Properties

| | |
|------------------------------|--------------|
| Appearance | Beige liquid |
| Specific weight at 20°C kg/l | 0.730 |
| Flash point °C | -10°C |

METHOD

ASTM D1298

ASTM D92

Specific Applications

- Ideal to protect machinery and pieces during road, rail or sea transport.
- For machine tool worktables.
- Tractors, Earth moving machines, exposed for long periods in the open air.

DIRECTIONS FOR USE

- Cup Gun
- Spray
- With Brush

N.B.: Always use neat. Shake the drum well before use. If the room is cold, keep for at least one day in a heated room.

Packaging available

5l

The information in this technical sheet is based on the specifications and potential use known to us. However, this data does not imply any legal obligation or liability whatsoever.

REGISTERED OFFICE
Via Domenico Scarlatti, 26
20124 Milan



Commercial Offices and Plant
Corso Europa, 91 – 20020 Solaro (MI)
info@farmicol.com
Customer Service +39 02 84505409
www.faren.com