

SILICONE OIL SPRAY (Registration NSF n°159268)

DESCRIPTION

It lubricates both at low and high temperatures. Excellent anti-noise and anti-creak effect. It protects and nourishes rubbers; it gives a hydro repellent protection on fabrics also rubberized ones; anti-oxidant for metals and steels. Odorless and colorless.

CONCENTRATED
WATER REPELLANT
POLISHING - LUBRIFICANT



Nonfood Compounds Program Listed H1
Registration No 159268

Suggestions for use:

Temperature range: > -38° C - +270° C.

Excellent in sailing, electric sector, printing sector. Very appreciated by campers and athletes as waterproof product. In DIY it can be used to polish, lubricate joints and rolling shutters etc.

HOW

Lubricant – Protective: spray directly on the surface from a distance of about 20 cm.

Waterproof and polishing agent: spray directly on the surface and clean with a clean cloth; or spray on a cloth and distribute homogeneously on the surface.

Available packaging: Spray 400 ml

The information in this technical sheet is based on the specifications and potential use known to us. However, this data does not imply any legal obligation or liability whatsoever

Chemical-physical properties

Color and aspect	Colorless liquid
Specific weight	0,61 kg/lit (liquid state)
Odor	Typical

Production

FARMICOL SPA
Corso Europa, 85-91 – 20020 Solaro (MI) Italy
info@farmicol.com - +39 02 84505



Worldwide Distributor

MAF CHEMICAL SA
Corso San Gottardo, 54 – 6830 Chiasso (CH)
export@maf-sa-ch

