


**Description**
**EXTRA TECHNICAL ZINC**

Over 98% pure, micronised, lamellar zinc-based and mixed with lamellar aluminium powder (to give the light colour). Guarantees longlasting protection against corrosion and oxidation, even externally.

**Details**
**Product specifications**
**INFO**
**PERFORMANCE**

21 micron of protection – resists up to 700°C – yield of 2,5m per aerosol

**RAPID**

Dust free and workable after 120 seconds

**PRACTICAL**

The nozzle can be rotated to dispense vertically and horizontally.

**Physical-Chemical Properties**

Colour and Appearance

**Product in its liquid state**

Light zinc liquid

Specific weight

0,78 kg/l

Fragrance

Characteristic

**Recommended use**

Equipped with a special, 360° valve that guarantees the zinc is dispensed completely, even in different positions. In addition, the dispenser valve has a very useful, rotating nozzle for a complete zinc paint treatment, which envisages 2 crossed coats, 10 minutes apart (horizontal + vertical). Dust free after 120", it finally catalyses within 12h.

**HOW TO USE**

Shake the aerosol vigorously so the two mixer balls inside mix the zinc powder well with the solvents and bonding resins. Dispense F98 evenly on the perfectly CLEAN, DRY surface to be treated.

**Packaging available**

400ml Spray

The information in this technical sheet is based on the specifications and potential use known to us. However, this data does not imply any legal obligation or liability whatsoever.

REGISTERED OFFICE  
Via Domenico Scarlatti, 26  
20124 Milan



Commercial Offices and Plant  
Corso Europa, 91 – 20020 Solaro (MI)  
[info@farmicol.com](mailto:info@farmicol.com)  
Customer Service +39 02 84505409  
[www.faren.com](http://www.faren.com)