



Description

ACRYLIC PAINT

Very thick acrylic enamel for ferrous surfaces.
In the colours: **Light grey - Forge grey - Graphite.**

Details

Product specifications

Product specifications

VERY THICK

LONGLASTING PROTECTION

Physical-Chemical Properties

Colour and Appearance Liquid

Specific weight 0.75 +/- 0.80 kg/l

Fragrance Typical solvent

Pressure at 20° C 4.0 +/- 0.5 bar

Thickness 1 coat 25 micron

Thickness 2 coats 50-60 micron

Pressure at 50° C 8.0 +/- 0.5 bar

Ford 4 Viscosity cup 12"

Gran. According to the Grindometer From 8 to 23 micron

Gloss Shine grade From 7 to 45 Gloss

Heat resistance 100 – 130°C

Drying time Dust free: 10 minutes

INSTRUCTIONS

- Apply on clean, dry surfaces.
- Vigorously shake the aerosol for one minute upside down.
- Spray thinly from a distance of approximately 20-30 cm.
- Wait a few minutes before repeating the treatment in the opposite direction (vertical-horizontal)

Directions for use

APPLICATIONS

- GATES
- FLASHING
- FERROUS PIPES
- SCAFFOLDING
- DRAIN PIPES
- DOORS

Packaging available

400ml.

The information in this technical sheet is based on the specifications and potential use known to us. However, this data does not imply any legal obligation or liability whatsoever.

REGISTERED OFFICE
Via Domenico Scarlatti, 26
20124 Milan



Commercial Offices and Plant
Corso Europa, 91 – 20020 Solaro (MI)
info@farmicol.com
Customer Service +39 02 84505409
www.faren.com