

**Description****TRANSPARENT SILICONE GREASE****Details**

To lubricate valves, taps, chains, roller tables, mould anti-adhesive, electric and electronic assembly, insulators, joints, brackets, seals, vacuum bell-jar covers, probes.

PHYSICAL-CHEMICAL AND TECHNICAL PROPERTIES

Properties	Description	Properties	Description
Appearance	Ointment	Acid and alkali resistant	Good
Colour	Translucent	Humidity resistant	Excellent
Density at 20 °C	0.970	Sea water resistant	Excellent
Dielectric strength (kw/mm)	>=15	Polar solvent resistant	Excellent
Temperature intervals	-50°/+250°C		

Important notes:

- Chemically safe and inert
- Water repellent
- Excellent humidity resistance
- Antistatic
- Resists soft and salt, hot and cold water, condensate, weak acids and alkali.
- High dielectric strength which makes it suitable as a dielectric seal for live equipment.

Directions for use

Clean the parts to be treated from any residue of grease or lubricant used previously.
Evenly apply with a spatula or hard bristle brush to the required thickness.

Packaging available

125-500-1000ml

The information in this technical sheet is based on the specifications and potential use known to us. However, this data does not imply any legal obligation or liability whatsoever.

REGISTERED OFFICE
Via Domenico Scarlatti, 26
20124 Milan



Commercial Offices and Plant
Corso Europa, 91 – 20020 Solaro (MI)
info@farmicol.com
Customer Service +39 02 84505409
www.faren.com