

**Description****UNIVERSAL LITHIUM GREASE**

To lubricate vehicles, self-propelled and fixed work-site industrial machinery. For hinges, gears, locks, pins, wheel hubs, skids, cables, sheaths, etc.

**Details****PHYSICAL-CHEMICAL AND TECHNICAL PROPERTIES**

Properties	Description	Properties	Description
Appearance	Ointment	Drop point ASTM D566	190°C
Colour	Beige	Worked penetration after 60 strokes	280 mm <sup>2</sup>
NLGI consistency number	2	Worked penetration after 100,000 strokes	292 mm <sup>2</sup>
Thickener type	Lithium	Welding load IP 239	120 kg
Temperature intervals	-25°/+120°C		

**Important notes:**

- Excellent resistance to oxidation
- Good anti-wear, anti-corrosion and anti-rust properties
- Good adhesive strength
- Is not washed away by water
- Wide operational temperature range
- Considerable mechanical stability and lubricant strength

**Directions for use**

Clean the parts to be treated from any residue of grease or lubricant used previously.  
Evenly apply with a spatula or hard bristle brush to the required thickness.

**Packaging available**

125-500-1000ml

The information in this technical sheet is based on the specifications and potential use known to us. However, this data does not imply any legal obligation or liability whatsoever.

REGISTERED OFFICE  
Via Domenico Scarlatti, 26  
20124 Milan



Commercial Offices and Plant  
Corso Europa, 91 – 20020 Solaro (MI)  
[info@farmicol.com](mailto:info@farmicol.com)  
Customer Service +39 02 84505409  
[www.faren.com](http://www.faren.com)