

**Description****GREASE FOR BEARINGS**

Fulfills the requirements for lubrication under “extreme pressures”. Ideal to lubricate BEARINGS with sliding and rolling friction subject to high loads and vibrations.

Details**PHYSICAL-CHEMICAL AND TECHNICAL PROPERTIES**

Properties	Description	Properties	Description
Appearance	Ointment	Drop point ASTM D566	190°C
Colour	Beige	Worked penetration after 60 strokes	280 mm ²
NLGI consistency number	2	Worked penetration after 100,000 strokes	292 mm ²
Thickener type	Lithium	Welding load IP 239	270 kg
Temperature range	-25°/+120°C		

Important notes:

- High resistance to mechanical stress and heavy loads
- Excellent resistance to oxidation
- Excellent anti-wear, anti-corrosion and anti-rust properties
- Excellent adhesive strength
- Is not washed away by water
- Wide operational temperature range

Directions for use

Clean the parts to be treated from any residue of grease or lubricant used previously.
Evenly apply with a spatula or hard bristle brush to the required thickness.

Packaging available

125-500ml.

The information in this technical sheet is based on the specifications and potential use known to us. However, this data does not imply any legal obligation or liability whatsoever.

REGISTERED OFFICE
Via Domenico Scarlatti, 26
20124 Milan



Commercial Offices and Plant
Corso Europa, 91 – 20020 Solaro (MI)
info@farmicol.com
Customer Service +39 02 84505409
www.faren.com