

**Description****MOLYBDENUM DISULPHIDE GREASE**

Particularly suitable for lubricating parts subjected to very difficult conditions. Lubrication of bearings, articulated joints, discs bearings, joints, gear wheels, skids, articulated arms, pulleys, buckets, etc.

Details**PHYSICAL-CHEMICAL AND TECHNICAL PROPERTIES**

| Properties | Description | Properties | Description |
|-------------------------|-------------|----------------------|-------------|
| Appearance | Ointment | Drop point ASTM D566 | 180°C |
| Colour | Black | Worked penetration | 265/295 dmm |
| NLGI consistency number | 2 | ASTM D217 | |
| Thickener type | Lithium | | |
| Temperature range | -20°/+140°C | | |

Important notes:

- Excellent anti-wear protection
- Maintains lubricant strength
- High stability of lubricant properties over time
- Is not washed away by water
- Wide operational temperature range
- Considerable mechanical stability and lubricant strength
- Good resistance to heavy loads and vibrations

Directions for use

Clean the parts to be treated from any residue of grease or lubricant used previously.
Evenly apply with a spatula or hard bristle brush to the required thickness.

Packaging available

125-500-5000ml

The information in this technical sheet is based on the specifications and potential use known to us. However, this data does not imply any legal obligation or liability whatsoever.

REGISTERED OFFICE
Via Domenico Scarlatti, 26
20124 Milan



Commercial Offices and Plant
Corso Europa, 91 – 20020 Solaro (MI)
info@farmicol.com
Customer Service +39 02 84505409
www.faren.com