



Description

INDEPTH PRIMER

Water-based treatment to deep clean absorbent terracotta and natural stone to improve yield and application of a subsequent treatment.

Details

Product specifications

BREATHABLE

ECOLOGICAL

ANTI-SALTS

Physical-Chemical Properties

	Product	Material	Yield
Colour and Appearance	Milky liquid	Marble granite	8-10 m ² /l
Specific weight	0.995 kg/l	Limestone	4-8 m ² /l
Fragrance	Characteristic	Terracotta	4-6 m ² /l
Flash point and boiling point	> 100°C		

HOW TO USE

- Apply on perfectly clean, dry surfaces.
- Apply the product evenly.
- Leave to dry 3-4 hours before applying a second coat.

N.B.: For highly porous surfaces, we advise applying two coats of the product wet on wet until the surface is saturated. Avoid creating stagnant surface water.

Recommended use

APPLICATIONS

Floors - Bricks
 Aggregates - Classic, Rustic and Old Terracotta - Limestone
 Travertine - Marble and Granite.

N.B.:

The product is READY-FOR-USE. Drying time is approximately 12 hours at 25°C and 24 hours at 15°C.
 Do not apply at temperatures below 10°C and in direct sunlight.
 During drying, protect the surface from water and humidity.
 The product can be applied with: Short pile paint roller –Spraying machine.

Packaging available

750ml

The information in this technical sheet is based on the specifications and potential use known to us. However, this data does not imply any legal obligation or liability whatsoever.

REGISTERED OFFICE
 Via Domenico Scarlatti, 26
 20124 Milan



Commercial Offices and Plant
 Corso Europa, 91 – 20020 Solaro (MI)
info@farmicol.com
 Customer Service +39 02 84505409
www.faren.com