



## Description

## EPOXY GLUE

Instant double component adhesive in syringe, with high tensile strength and resistant to high temperatures.  
For Indoor and Outdoor use.

## Details

## Product specifications

## INFO

WORKABLE

Can be drilled, sandpapered and painted.

TRANSPARENT

Does not discolour over time.

RESISTANT

Strong and robust, it is water resistant.

## Physical-Chemical Properties

Colour and Appearance

Product

Colourless liquid

Flash point

1.6 kg/l

Fragrance

Characteristic

## Recommended use

**FOR CERAMICS - BRICKWORK - WOOD - MARBLE - FIBRE GLASS METAL - PLASTIC.** Ideal for repairing jewellery

- The surface must be clean and dry.
- Cut the tip of each nozzle.
- Dispense the same quantity of resin and hardener.
- Clean the nozzles and close each one with the appropriate cap.
- Mix well and use within 3 minutes.

## Packaging available

25ml

The information in this technical sheet is based on the specifications and potential use known to us. However, this data does not imply any legal obligation or liability whatsoever.

REGISTERED OFFICE  
Via Domenico Scarlatti, 26  
20124 Milan



Commercial Offices and Plant  
Corso Europa, 91 – 20020 Solaro (MI)  
[info@farmicol.com](mailto:info@farmicol.com)  
Customer Service +39 02 84505409  
[www.faren.com](http://www.faren.com)