



Description

UNIVERSAL WATER REPELLENT

Specific for external coverings (exposed facade, exposed cement, bricks) Prevents absorption of water and humidity.

Details

Product specifications

RESISTS UV RAYS

ODOURLESS

DOES NOT DISCOLOUR

Physical-Chemical Properties

	Product	Material	Yield
Colour and Appearance	Colourless liquid	Marble Granite Slate	8-15 m ² /l
Specific weight	0.790 kg/l	Limestone	4-8 m ² /l
Fragrance	Characteristic	Bricks	3-5 m ² /l
Flash point	> 21°C		

Correctly applied (with two coats) and maintained, it can last up to 48 months. Not acid proof.

INSTRUCTIONS

- Apply on perfectly clean, dry surfaces. (wash with POWER CLEAN at 4% in water, wait 3-4 days until completely dry)
- Apply the product evenly.
- Use a cloth to avoid residue or drips.
- Leave to dry at least 6 hours before applying a second coat of the product.

Recommended use

APPLICATIONS

Exposed facades - Exposed cement - Columns - Bricks - Agglomerates - Slate - Limestone - Travertine, marble and treated granite - Balustrades.

N.B.:

The product is READY-FOUSE. Drying time is approximately 12 hours at 25°C and 24 hours at 15°C. Do not apply at temperatures below 10°C and in direct sunlight. During drying, protect the surface from water and humidity. The product can be applied with: Short pile paint roller – Brush - Spraying machine.

Packaging available

1-5l

The information in this technical sheet is based on the specifications and potential use known to us. However, this data does not imply any legal obligation or liability whatsoever.

REGISTERED OFFICE
Via Domenico Scarlatti, 26
20124 Milan



Commercial Offices and Plant
Corso Europa, 91 – 20020 Solaro (MI)
info@farmicol.com
Customer Service +39 02 84505409
www.faren.com