

**Description****ACRYLIC PAINT**

Acrylic enamel available in the following versions:  
**Transparent: Glossy and Matt**

**Details****Product specifications****Product specifications**

EXCELLENT ADHESIVENESS

PROTECTS FROM OXIDATION

**Physical-Chemical Properties**

Colour and Appearance Liquid

Specific weight 0.75 +/- 0.80 kg/l

Fragrance Typical solvent

Pressure at 20°C 4.0 +/- 0.5 bar

Thickness 1 coat 5 micron

Thickness 2 coats 15 micron

Pressure at 50°C 8.0 +/- 0.5 bar

Ford 4 Viscosity cup 11"

Gran. on the Grindometer From 8 to 10 micron

Gloss Shine grade 90 Gloss

Heat resistance 100-12°C

Drying time Dust free: 10 minutes

**INSTRUCTIONS**

- Apply on clean, dry surfaces.
- Vigorously shake the aerosol for one minute upside down.
- Spray thinly from a distance of approximately 20-30 cm.

**Directions for use****APPLICATIONS**

- ORNAMENTS
- CERAMIC TILES
- WOOD AND PLASTIC PRODUCTS

**Packaging available**

400ml

The information in this technical sheet is based on the specifications and potential use known to us. However, this data does not imply any legal obligation or liability whatsoever.

REGISTERED OFFICE  
 Via Domenico Scarlatti, 26  
 20124 Milan



Commercial Offices and Plant  
 Corso Europa, 91 – 20020 Solaro (MI)  
[info@farmicol.com](mailto:info@farmicol.com)  
 Customer Service +39 02 84505409  
[www.faren.com](http://www.faren.com)