



Description

CONSOLIDATING EFFECT

Blocks characteristic crumbling of stone, marble and soft surfaces which deteriorate when in contact with water and humidity and become weak and crumbly.

Details

Product specifications

ANTI-FREEZE - ANTI-MOULD

DOES NOT DISCOLOUR

BREATHABLE

Physical-Chemical Properties

Colour and Appearance

Product

Yellowish liquid

Material

Marble Granite

Yield

8-10 m²/l

Specific weight

0.955 kg/l

Slate

4-8 m²/l

Fragrance

Characteristic

Flash point

> 21°C

Correctly applied (with two coats) and maintained, it can last up to 36 months. Not acid proof.

HOW TO USE

- Apply on perfectly clean, dry surfaces (remove any dust, crumbled material or dirt before treatment).
- Apply the product every 30 minutes with a short bristle paint brush to guarantee better penetration until the support surface is completely saturated.

Recommendations

APPLICATIONS

Floors - Columns Windowsills - Balustrades and Mosaics – Urban Furnishing

MAINTENANCE

Once every six months: Clean with POWER CLEAN

NOTES

The product is READY-FOR-USE. Drying time is approximately 12 hours at 25°C and 24 hours at 15°C. Do not apply at temperatures below 10°C and in direct sunlight. During drying, protect the surface from water and humidity.

Packaging available

750ml

The information in this technical sheet is based on the specifications and potential use known to us. However, this data does not imply any legal obligation or liability whatsoever.

REGISTERED OFFICE
Via Domenico Scarlatti, 26
20124 Milan



Commercial Offices and Plant
Corso Europa, 91 – 20020 Solaro (MI)
info@farmicol.com
Customer Service +39 02 84505409
www.faren.com