



Description

DENSE GEL PAINT STRIPPER

Penetrates the layer of resin to remove it from the support layer by characteristically re-inflating it. Finally, it softens it, thus making it easy to remove.

Details

Product specifications

NO R₄₀ - NO
DICHLOROMETHANE

SAFE

INFO

Does not contain R₄₀ classified
solvents eand does not contain
Dichloromethane

For operators

Physical-Chemical Properties

Colour and Appearance

Product in its liquid state

Colourless viscous liquid

Specific weight

N.D.

Fragrance

Characteristic

Recommended use

Tests have shown the following results for speed of action:

Strong Industrial Paint:	within 3 minutes
Nitrocellulose Enamel:	within 3 minutes
Primer:	within 15 minutes ca.
Powder Paint:	from 6 to 12 minutes
Paint for wooden shutters:	30-60 seconds

HOW TO USE

Use a paint brush and apply on the object. Wait for the product to finish working and then remove the paint.

Packagings available

750ml – 5l

The information in this technical sheet is based on the specifications and potential use known to us. However, this data does not imply any legal obligation or liability whatsoever.

REGISTERED OFFICE
Via Domenico Scarlatti, 26
20124 Milan



Commercial Offices and Plant
Corso Europa, 91 – 20020 Solaro (MI)
info@farmicol.com
Customer Service +39 02 84505409
www.faren.com